framatome

PWR Head Examination and Repair

Reactor Vessel Closure Head Volumetric Exams including Bare Metal Visuals & CO₂ Cleaning

Utilities can manage their reactor vessel closure head inspection with confidence thanks to Framatome's wide range of inspection and repair tools

Challenge


Compliance and inspection in the nuclear industry require top-of-the-line resources for success. Utilities need the right tools to get the job done safely and effectively. Complying with Code Case N-729 and the periodic examinations of the reactor vessel closer head (RVCH) penetrations requires specific tools to ensure quality inspections at all plants.

Solution

When the industry's best tools are required, Framatome has you covered. Utilities can manage their RVCH penetration inspections with confidence thanks to Framatome's wide range of inspection and repair tooling for a variety of needs. Flexible inspection tools promote safety and efficiency — plus, our tools are tested and used successfully in the industry to help eliminate unplanned outages. In addition, the right delivery system can eliminate dose and minimize schedule impact for manipulator exchange.

Customer benefits

- NUMAN under-head manipulator delivers a variety of inspection and repair tools
 - Low-profile carriage reaches out of the head-stand opening for a low-dose tool change
 - Encoded positioning enables inspection traceability
 - Graphical user interface with collision avoidance promotes safe, efficient operation
- Minimize dose and schedule impact for manipulator exchange with available repair tools, if needed, delivered using the same NUMAN platform



Your performance is our everyday commitment



Raptor-Remote PT application




Jamko's THOR inspection crawler and bare metal visual inspection system




Jamko's CO₂ machine for CO₂ dry ice cleaning process



Apache-Remote PT application



Bottom-Up Tool inspects vent lines and nozzles without thermal sleeves



Dual Blade Probe provides both circumferentiallyand axially-oriented TOFD UT inspections. The design features maximum flexibility for the most complete coverage — even on extreme peripheral nozzles.

Field-hardened and tested equipment leads to predictable outages

Contact:

examination@framatome.com

www.framatome.com

The data and information contained herein are provided solely for illustration and informational purposes and create no legal obligations by Framatome Inc. None of the information or data is intended by Framatome Inc. to be a representation or a warranty of any kind, expressed or implied, and Framatome Inc. assumes no liability for the use of or reliance on any information or data disclosed in this document. ©2019 Framatome Inc. All rights reserved. PS_US_399_ENG_04-19

